

MIRAGE® DATA

PRODUCT COMPOSITION

Surface Coating	Aqueous Polyurethane
Base Material	Latex Impregnated Paper
Process of Production	Chemical Pulp

	DOMESTIC	INTERNATIONAL
Average Weight	127# (24x36)	207gsm
Average Thickness	.009"	.229 mm


ROLL DIMENSIONS

	DOMESTIC	INTERNATIONAL
Width	56"	1,422.4 mm
Roll Length	250 yds	100 mtrs
Roll Weight	160 lbs	30.4 kg
Core Size	3"	7.62 cm

ORDERING INFO

	DOMESTIC	INTERNATIONAL
Minimum Order Quantity (Stock)	50 yds	50 mtrs
Minimum Order Quantity (Custom)	1000 yds	1000 mtrs
Stock Sample Size (Grain Short)	18 x 12" 26 x 20"	45.72 x 30.48mm 66.04 x 50.8mm
Standard Wind Up	Face Out	Face Out
Harmonized Tariff Code		4811.90.3000

APPLICATIONS



Decoration Foil Stamp, Blind Stamp, Silk Screen

Recommended Gluing Back & Face: PVA/Synthetic

BRANDING RECOMMENDATIONS*

	DOMESTIC	INTERNATIONAL
Stamping Temperature	275 – 300° F	135 – 149° C
Stamping Pressure	60 – 80 lbs/in ²	4.21 – 5.63 kg/cm ²
Dwell Time	0.5 – 1 Second	0.5 – 1 Second

Recommended Die Type Teflon Coated Magnesium

*Branding conditions will vary on different types of Stamping Machines, please request samples of Aurora to test your process

SUSTAINABILITY

